

PLASTISOL FP2/3005A FLASH WHITE

PRODUCT DESCRIPTION

Plastisol inks suitable for textile printing.
White suitable for underlay printing.
White with a bright finishing.

GENERAL FEATURES

- High opacity
- Suitable for underlay printing onto dark substrates
- Soft touch
- Good elasticity
- Quick intermediate flash cure
- Polymerization at 150/160°C for 3 minutes
- Low tack
- Phthalate-free

PREPARATION

Ready to use.
Homogenize before using.
Check Viscosity according the job.

APPLICATION

In order to achieve the best opacity and brightness we recommend adjusting the out of contact and the squeegees pressure. We advise to use as photo-emulsion **VARIOCOAT 10019, VARIOCOAT 10830, VARIOCOAT 10850, ULANO QLT, ULANO PROCLAIM, ULANO QX-3.**

FLASH WHITE can be printed from 34 to 90 mesh.

POLYMERIZATION

Curing has to take place at 150/160°C for 2-3 minutes.

CLEANING

Wash tools with **VARIOWASH 2647**
We have **BIODEGRADABLE** solvent for cleaning, recommended for use in recirculation system (**VARIOCLEAN**).

PACKAGE

1 – 7 KG.

SPECIAL INSTRUCTIONS

- Always check curing temperature; only an appropriate curing is able to allow the complete ink fusion and so the achievement of the required final characteristics.
- Plastisol inks do not resist to dry cleaning, bleaching, and ironing.